

Single Scrabblor

Application :

Teryair X 2 Single Scrabblor removes heavy rust and scale by impacting action of a single reciprocatory piston. It is used where there is a need to break through heavy and stubborn layers of rust or chemical coatings.

Features :

Twist type throttle. Special chomemolybednum piston material, simple one moving part mechanism, easy to maintain, light weight, easy to maneuver.

Technical Data :

Model No : X 2

IMPA No. : 59.03.82

Net Weight : 2.2 Kgs.

Overall Length : 500 mm

Frequency : 3900 bpm

Air Consumption : 5 cfm

Air inlet pressure : 90 psig

Throttle Type : Twist

Piston Tip Material : Chromium Molybdenum Steel

Air Inlet : 3/8" BSP



Model : X 2

Teryair Equipment Pvt. Ltd.

An ISO 9001-2008 company

Sales Office: 416, Gundecha Industrial Complex,
Akurli Road, Kandivali East, Mumbai - 400 101
Maharashtra, India

Tel : +91 22 421 04 901 (20 Lines)

Fax : +91 22 421 04 909

Email : sales@editool.in
Info@teryair.com

Works: A-1, Tirupati Udyog Nagar, Sativali Road,
Vasai East, Thane - 401 208 Maharashtra, India

Tel : +91 250 6455260 (32 Lines)

Fax : +91 250 2450 693

Email: toolsales@teryair.com
Info@teryair.com

www.teryair.com

